

Maximum capacity 140 kg, up to 4.9 meters in height

The lift CM 520 allows you to safely maneuver loads at height.

The lift that best adapts to any situation.

Small and portable, suitable for any type of intervention, even the fastest.

Model	Base Height	Height of work max	Load highs	Weight	Dimensions feet closed	Dimensions open feet
CM 520	1,18 mt	4,9 mt	140 kg a 3,0 mt 130 kg a 4 mt 90 kg a 4,9 mt	38 kg	380 x 380 mm	1,4 x 1,5 mt



Ruote per il trasporto
tipo trolley (di serie)




STRUCTURE


- Telescopic pole in high temperature treated aluminum
- Quick in use and positioning
- Possible use on slopes of the on the ground or on stairs, simply adjusting the height of the feet
- Special UPTER system, adjustment to work close to walls
- 230 V electric motor with variable speed drive speed
- Can also be used in the event of a power failure, using the handle provided (or screwdriver)
- Integrated torque limiter, which protects the motor in case of overload
- 360° rotating platform (440 x 750 mm) with multi-locking positions
- Transportable as a trolley



ACCESSORIES




Support for plasterboard
for assembly slab ceiling



Stretching platform
2 x 380 mm



GLS suction cup
for assembly of glass on the roof



GL V LX suction cup
Ideal for the assembling of roof windows

Technical features




Manual use
With crank provided



A resealable foot
To place it close to walls



Four extendable feet
For work on slopes



Bubble level
Control of the perfect positioning of the loads

